

PRODUCT INFORMATION

NO. N221C

Double-coated adhesive tape

Features/characteristics

1. Adhesive : High -tack Acrylic (Solvent base) adhesive.
2. Carrier : Cross-Linked 4 PCF PE Foam.
3. Liner : 90g/m² Glassine Paper - white color.
4. Quick stick and moderate shear strength for efficient operation.
5. Flexible Foam material to provide comfortable mating to contour surface.

Technical data

- | | |
|-----------------------------|--|
| 1. Thickness : | 1.0 ± 0.1 mm |
| 2. Tack : J. Dow No. | 25 |
| 3. Peel Adhesion : PSTC - 3 | 2.1 kg / 25 mm |
| 3. Shear Strength : | Over 24 hrs with 1 kg loading on 25mm x 25mm sandwich holding of 2 stainless steel plates at 25 °C |
| 4. Service Temperature : | - 20°C ~ 80°C |

Applications

1. Fastening & joining to nameplates, plastic parts, signs and emblems.
2. Permanent fixing result for metal, wooden or plastic articles.

Remark

All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty. It's essential that the user should evaluate the product for a period of time to determine whether it is fit for a particular purpose and suitable for the user's method of application.



Devtec Technological Adhesives Ltd.

P.O.B 1397 Hod Hasharon 45112
Offices: 19 Alexander Yanai St., Petach Tikva, ISRAEL
Tel.+972-3-9306694 Fax.+972-3-9043717

www.devtec.co.il sales@devtec.co.il

דבטק דבקים טכנולוגים בע"מ

למכתבים: ת.ד. 1397 הוד השרון 45112
משרדים: אלכסנדר ינאי 19, פתח תקוה
טל'. 03-9306694 פקס. 03-9043717



Devtec Technological Adhesives Ltd.

P.O.B 1397 Hod Hasharon 45112
Offices: 19 Alexander Yanai St., Petach Tikva, ISRAEL
Tel.+972-3-9306694 Fax.+972-3-9043717

www.devtec.co.il sales@devtec.co.il

דבטק דבקים טכנולוגים בע"מ

למכתבים: ת.ד. 1397 הוד השרון 45112
משרדים: אלכסנדר ינאי 19, פתח תקוה
טל'. 03-9306694 פקס. 03-9043717