

TECHNICAL CHARACTERISTICS

DV 6000

STICK HOT-MELT Ø 11,5 mm.

FAST JOINING OF PAPER AND BOARD MATERIAL

• COLOUR.....	LIGHT BROWN
• VISCOSITY (CPS) (180 °C).....	4.000
• DENSITY (grs/cm ³) (23 °C).....	0,98
• RING AND BALL (R & B) (°C).....	95/100
• OPEN TIME (SECONDS).....	8/12
• APPLICATION TEMP. (°C).....	180/210
• TENSILE (Kg/cm ²) (20 °C).....	42
• SHEAR (Kg/cm ²). (20 °C).....	45
• ELONGATION (%).....	250

NOTE: Inert adhesive at room temperature. Contact with molten product will cause burns.



Devtec Technological Adhesives Ltd.

P.O.B 1397 Hod Hasharon 45112
Offices: 19 Alexander Yanai St., Petach Tikva, ISRAEL
Tel.+972-3-9306694 Fax.+972-3-9043717

www.devtec.co.il sales@devtec.co.il

דבטק דבקים טכנולוגים בע"מ

למכתבים: ת.ד. 1397 הוד השרון 45112
משרדים: אלכסנדר ינאי 19, פתח תקוה
טל'. 03-9306694 פקס. 03-9043717