

PRODUCT DATA SHEET



0390

Version No.1

Revision Date: 01/05/12

Page 1 of 2

DESCRIPTION

0390 is a high performance butyl tape.

KEY FEATURES

Good adhesion to a wide range of substrates.

Good UV resistance.

Highly conformable.

Carefully selected fillers provide the product with good chemical resistance.

Remains flexible throughout its service life.

Easy and accurate to use with little or no mess.

USES

For use as a gap-filling sealant in body-in-white applications on vehicles.

For sealing a variety of joints in roofing and cladding systems.

For sealing joints in more aggressive environments, such as slurry tanks.

PERFORMANCE

	UNIT	NOMINAL VALUE	TEST METHOD
Dynamic Tensile Adhesion	N/cm ²	20	H5
Dynamic Shear Adhesion	N/cm ²	15	H15
90 ° Peel Adhesion	N/cm	12	H48
180 ° Peel Adhesion	N/cm	18	H41
Specific Gravity	g/cm ³	1.1	H6
Moisture Vapour Transmission Rate	g/m ² /24hr/mm	0.13	ISO9932 / BS ISO 15106
Service Temperature Range	°C	-40 to +90	

H – HS Butyl Test Method

Gordleton Industrial Park,
Hannah Way, Sway Road,
Lymington, Hampshire,
SO41 8JD, UK.



T: +44 (0)1590 684400
F: +44 (0)1590 683728
E: sales@hsbutyl.com
W: www.hsbutyl.com

PRODUCT DATA SHEET



0390

Version No.1

Revision Date: 01/05/12

Page 2 of 2

APPLICATION

PROPERTIES

Application temperature range: +5°C to +40°C

Shelf life: 24 months when stored flat in original packaging in cool, dry conditions.

INSTRUCTIONS

Surface preparation: All surfaces should be clean, dry and free from frost, grease and loose materials. When cleaning contaminated substrates, HS Butyl recommend that propan-2-ol (IPA) is used and allowed to dry prior to the application of the butyl tape.

Application: Apply direct from the reel onto one surface and press sufficiently along its whole length to achieve good initial adhesion. Remove backing paper and offer other surface to the butyl tape and push firmly to seal across the joint.

PACKAGING

The product is normally supplied as a preformed strip on a siliconised release paper. A wide range of dimensions can be supplied. Product dimensions will determine the number of rolls per carton.

Available colours: Black.

TOLERANCES

Rectangular sections:

Thickness $\pm 10\%$

Width: up to 25mm $\pm 1\text{mm}$

26mm to 100mm $\pm 2\text{mm}$

over 100mm $\pm 3\text{mm}$

Bead sections:

Thickness $\pm 10\%$

Width $\pm 10\%$

GENERAL

0390 butyl tape is part of a range of butyl products for Construction, Automotive & specialist markets. For further information, please contact our Customer Care Team or visit our Website.

The information given in this product data sheet is based on laboratory tests and experience which we believe to be correct. Properties quoted are typical and do not therefore constitute a specification. In view of the wide range and variability of substrates, we would advise that our product should be tested by the user to establish suitability for its intended application. E & OE.

Gordleton Industrial Park,
Hannah Way, Sway Road,
Lymington, Hampshire,
SO41 8JD. UK.



T: +44 (0)1590 684400
F: +44 (0)1590 683728
E: sales@hsbutyl.com
W: www.hsbutyl.com